

Liefer- / Lagerprogramm

Schleifhülsen zylindrisch und konisch + zugehörige Schleifbandkörper (GK)

mit 3, 6 und 8 mm Schaft

Normalkorund, Zirkon, Innox, Keramik

Abmessung=mm D x T	VE Stück	GK-Schaft mm	U/max.	NORMALKORUND						INOX Körnung	ZIRKON Körnung	Keramik Körnung
				Körnung								
				40	50	60	80	150	240			
4 x 10	100	3/6	55.000					x				
6 x 10	100	3/6	55.000					x				
8 x 10	100	3/6	55.000					x				
10 x 10	50	6	44.000		x		x	x				
10 x 20	50	6	44.000		x		x	x	x		50/80	
12 x 10	50	6	44.000									
12 x 25	50	6	44.000									
13 x 10	50	6	44.000		x		x	x				
13 x 25	50	6	44.000		x		x	x			50/60/80	
15 x 10	50	6	36.000		x	x	x	x				
15 x 30	50	6	36.000	x	x	x	x	x	x	50/80/150	50	60/80/120
19 x 25	50	6	30.000		x	x	x	x	x		40/50/60/80	
20/14 x 63	50	6	26.000	x		x	x	x	x			36/60/80/120
22 x 20	50	6	26.000	x	x	x	x	x	x	50/80/150	50	60/80/120
25 x 25	50	6	22.900		x	x	x	x	x		40/50/60/80	60/80/120
29/22 x 30	50	6	19.100	x	x	x	x	x	x	50	50	36/60/80/120
30 x 20	50	6	19.100	x	x	x	x	x			50	
30 x 30	50	6	19.100	x	x	x	x	x	x	36/50/80/150	40/50/60/80	36/60/80/120
36/22 x 60	50	6	15.900	x	x	x	x	x		50	50	36/60/80/120
38 x 25	50	6	15.900	x	x	x	x	x			40/50/60/80	
45 x 10	50	6	12.700									
45 x 30	50	6	12.700	x	x	x	x	x	x	36/50/80/150	40/50/60/80	36/60/80/120
51 x 25	50	6	11.200	x	x	x	x	x			40/50/60/80	
60 x 30	50	6/8	9.500	x	x	x	x	x	x	36/50/80/150	50	36/60/80/120
75 x 30	50	8	7.600	x	x	x	x	x				
100 x 40	50	8	5.700	x	x	x	x	x				