


Liefer- / Lagerprogramm

Schleifkappen + zugehörige Schleifbandkörper (GK)


mit 3 und 6 mm Schaft

Normalkorund, Siliciumkarbid, Keramik




Form A

Abmessung=mm D x T	VE Stück	GK-Schaft mm	U/max.	NORMALKORUND Körnung					Sic Körnung	Keramik Körnung
				60	80	120	150	280		
5 x 10	50	3	95.000		x	x	x	x		
7 x 12	50	3	65.000	x		x	x	x		
10 x 15	50	3	45.000	x		x	x	x		
13 x 17	50	6	35.000	x		x	x	x		
16 x 26	50	6	30.000	x		x	x	x		




Form C

5 x 11	50	3	95.000		x	x	x	x	80/150	80/120
7 x 13	50	3	65.000	x		x	x	x	80/150	80/120
10 x 15	50	3	45.000	x		x	x	x	80/150	80/120
13 x 17	50	6	35.000	x		x	x	x	80/150	80/120
16 x 26	50	6	30.000	x		x	x	x	80/150	80/120



Form G

5 x 11	50	3	95.000		x		x	x		
7 x 13	50	3	65.000	x			x	x		
10 x 15	50	3	45.000	x			x	x		
13 x 17	50	6	35.000	x			x	x		
16 x 26	50	6	30.000	x			x	x		



Form L

5 x 15	50	6	95.000		x		x	x	80/150	80/120
11 x 25	50	6	40.000	x			x	x	80/150	80/120
16 x 32	50	6	30.000	x			x	x	80/150	80/120
21 x 40	50	6	20.000	x			x	x	80/150	80/120